

# High-Security Composite Safes

## Gibraltar® TL-15, TL-30 & TL-30X6

When it comes to rock-solid security in the face of multiple threats, rely on Meilink®'s Gibraltar series to protect your most valued assets. All models carry the 1-hour Omega Point Laboratories Ω Fire label and are available in three increasingly secure TL burglary ratings, culminating in the six-sided protection of our TL-30X6 – the very best defense against the most intensive tool attacks. A variety of custom interiors is available for individual specifications.



Completely customizable interiors to fit any need.



### KX7233

Optional aluminum pull handle, tri-spoke handle and double-bitted key lock protected by a glass relocker.



### Gibraltar JC4524-Z

TL-15 is shown with an optional 8" pull handle. Three shelves are standard with this model.



### Gibraltar KC6524

TL-30 shown with optional electronic lock.



### Gibraltar KX7233SZ

TL-30X6 shown with optional tri-spoke handle, pull handle and secondary key lock.



## Accessories






The majority of Meilink® models come with multiple interior options, including lockers, extra shelves and drawers. Choose from pull handles and spoke handles to configure your safe for the job at hand. A wide variety of locking options can be tailored to your purpose, including time locks, auxiliary key locks and the latest in electronic locking options.



### KC6524


Shown with optional S & G electronic lock for dual control or day lock.

Meilink is the only manufacturer to offer a UL® fire label with the TL-15 or TL-30 burglary rating. Optional lockers and drawers are available on all models.

Name	Model	Shelves	Approx. Ship Weight (lbs.)	Interior Capacity (cu. ft.)	Interior Size			Exterior Size		
					Height	Width	Depth	Height	Width	Depth <sup>1</sup>
<b>Gibraltar</b>										
<b>TL-15</b>	JC1814-Z	1	785	1.8	18"	14"	12¼"	25"	21"	21¼"
	JC2218-Z	1	1068	3.8	22"	18⅝"	16"	28½"	25¼"	27"
	JC3020-Z	2	1585	7.3	30"	20"	21"	36½"	26⅝"	32"
	JC3624-Z	2	1975	10.5	36"	24"	21"	42½"	30⅝"	32"
	JC4524-Z	3	2267	13.1	45"	24"	21"	51½"	30⅝"	32"
	JC5524-Z	4	2642	16.0	55"	24"	21"	61½"	30⅝"	32"
	JC6033-Z	4	3583	24.7	60"	33⅞"	21"	66½"	41"	32"
	JC6524-Z	5	3080	19.0	65"	24"	21"	71½"	31⅝"	32"
	JC6528-Z	5	3591	22.1	65"	28"	21"	71½"	35⅝"	32"
	JC733SZ	5	3899	29.6	72"	33⅞"	21"	78½"	41"	32"
	JC733-Z	5	4543	36.7	72"	33⅞"	26"	78½"	41"	37"
<b>TL-30</b>										
	KC1814-Z	1	794	1.8	18"	14"	12¼"	25"	21"	21¼"
	KC2218-Z	1	1092	3.8	22"	18⅝"	16"	28½"	25¼"	27"
	KC3020-Z	2	1622	7.3	30"	20"	21"	36½"	26⅝"	32"
	KC3624-Z	2	2029	10.5	36"	24"	21"	42½"	30⅝"	32"
	KC4524-Z	3	2325	13.1	45"	24"	21"	51½"	30⅝"	32"
	KC5524-Z	4	2715	16.0	55"	24"	21"	61½"	30⅝"	32"
	KC6033-Z	4	3721	24.7	60"	33⅞"	21"	66½"	41"	32"
	KC6524-Z	5	3218	19.0	65"	24"	21"	71½"	31⅝"	32"
	KC6528-Z	5	3752	22.1	65"	28"	21"	71½"	35⅝"	32"
	KC7233SZ	5	4055	29.6	72"	33⅞"	21"	78½"	41"	32"
KC7233-Z	5	4709	36.7	72"	33⅞"	26"	78½"	41"	37"	
<b>TL-30X6</b>										
	KX3624-Z	2	2269	10.5	36"	24"	21"	42½"	30⅝"	32"
	KX4524-Z	3	2615	13.1	45"	24"	21"	51½"	30⅝"	32"
	KX5524-Z	4	3055	16.0	55"	24"	21"	61½"	30⅝"	32"
	KX6033-Z	4	4151	24.7	60"	33⅞"	21"	66½"	41"	32"
	KX6524-Z	5	3604	19.0	65"	24"	21"	71½"	31⅝"	32"
	KX6528-Z	5	4202	22.1	65"	28"	21"	71½"	35⅝"	32"
	KX7233SZ	5	4555	29.6	72"	33⅞"	21"	78½"	41"	32"
KX7233-Z	5	5254	36.7	72"	33⅞"	26"	78½"	41"	37"	


<sup>1</sup> Includes 1⅞" for door handles and dials

## Burglary Ratings

 The Lock Icon designates the safe's ability to protect against unauthorized entry and theft. The number represents the increasing level of burglary protection within the safe line.

These safes come with a lifetime replacement warranty in case of fire and a 1-year limited warranty.

## Fire Ratings

 The Fire Icon designates the safe's ability to protect against fire damage. The number in the icon represents the time frame of the test the safe has passed. Icons with a (+) represent that the safe has earned UL's impact rating.

**MEILINK**

101 Security Parkway • New Albany, IN 47150  
812-941-0024 • 1-800-MEILINK  
Fax 800-896-6606 • www.meilinksafe.com

Meilink is a member of the FireKing® Security Group.  
M-0406-01